



BURKERT Solenoid valve 3/2 fig. 33250 series 330 brass

Characteristics

Series: 330
Type: 33250
Model: Solenoid valve three way
Function: Normally closed [NC]
Actuation: Direct-acting
Orifice: 3 mm
Kvs value: 0.18 m³/h
Minimum pressure difference: 0 bar
Maximum pressure difference: 10 bar
Housing material: Brass
Material quality: CW617N [CuZn40Pb2]
Sealing: NBR
Material coil housing: Epoxy

Characteristics [2]

Material shorting ring: Copper
Working time: 100 %
Level of protection (IP value): IP65
Emergency manual operation: Yes
Explosion-proof: No
SIL certified: No
Medium temperature: From 0 °C to 80 °C
Ambient temperature: Not applicable

Process connection	Size process connection	Connection air exhaust[s]	Coil type	Supply voltage	Frequency	Electrical connection	Including plug	Power	Starting power	Article
Internal thread [BSPP]	1/4" [8]	1/4" [8]	SPC	24V AC	50Hz	Plug EN 175301-803 type A	No	8 W / 15 VA	30 VA	13340001
Internal thread [BSPP]	1/4" [8]	1/4" [8]	SPC	24V DC		Plug EN 175301-803 type A	No	11 W		13340003
Internal thread [BSPP]	1/4" [8]	1/4" [8]	SPC	230V AC	50Hz	Plug EN 175301-803 type A	No	8 W / 15 VA	30 VA	13339993

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.