



BURKERT Pilot valve Namur Type: 33570 series 6519 polyamide

Characteristics

Series: 6519
Type: 33570
Model: Namur 3/2 or 5/2 way
Process connection: NAMUR
Size process connection: 1/4" (8)
Air supply connection: Internal thread
Connection standard air supply: NAMUR (VDI/VDE 3845)
Connection air exhaust(s): Internal thread
Function: Mono-stable
Actuation: Indirect-acting
Including plug: No
Orifice: 6 mm
Kvs value: 0.8 m³/h

Characteristics (2)

Minimum pressure difference: 2 bar
Maximum pressure difference: 8 bar
Housing material: Polyamide
Sealing: NBR - PUR
Material coil housing: PA
Working time: 100 %
Level of protection (IP value): IP65
Explosion-proof: No
SIL certified: No
Medium temperature: -25 / 60 °C

Size of air supply connection	Diameter air exhaust	Coil type	Supply voltage	Frequency	Electrical connection	Power	Starting power	Emergency manual operation	Ambient temperature	Article
1/4" BSP	1/4" BSP	SPC	24V AC	50/60Hz	Plug EN 175301-803 type A	2 W	11 VA	Yes	From -25 °C to 55 °C	11815276
1/4" BSP	1/4" BSP	SPC	24V DC		Plug EN 175301-803 type A	2 W	11 VA	Yes	From -25 °C to 55 °C	13339971
1/4" BSP	1/4" BSP	SPC	230V AC	50/60Hz	Plug EN 175301-803 type A	2 W	11 VA	Yes	From -25 °C to 55 °C	13339969

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.