



LEADER PTFE flange gasket CLIPPERLON 2130 EN 1514-1



Characteristics

Series: CLIPPERLON

Type: 2130

Norm: EN 1514-1 IBC

Material structure: PTFE expanded

Marking: Printed

Temperature range: -240 / 230 °C

Max. pressure: 40 bar

Suitable for medium: Strong Alkalis, Alkalis, Cryogenic, Weak Alkalis, Chlorine, gaseous [7782-50-5], Solvents, Air [compressed air], Strong acids [except hydrofluoric], Hydrocarbons, Acids, Chlorine Water < 5% [7782-50-5], Refrigerants, Weak Acids

Approval according to: TA-Luft

Application

- Recommended in: Chemical

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN10	PN10/40	46	18	3	13366412
DN15	PN10/40	51	22	3	13366413
DN20	PN10/40	61	27	3	13366404
DN25	PN10/40	71	34	3	13366405
DN32	PN10/40	82	43	3	13366406
DN40	PN10/40	92	49	3	13366407
DN50	PN10/40	107	61	3	13366392
DN65	PN10/40	127	77	3	13366408
DN80	PN10/40	142	89	3	13366409
DN100	PN10/16	162	115	1.5	13366446
DN100	PN10/16	162	115	2	13366487
DN100	PN10/16	162	115	3	13366403
DN100	PN25/40	168	115	3	13366414
DN125	PN10/16	192	141	1.5	13366448
DN125	PN10/16	192	141	2	13366488
DN125	PN25/40	194	141	3	13366416
DN125	PN10/16	192	141	3	13366415
DN150	PN10/16	218	169	1.5	13366450
DN150	PN10/16	218	169	2	13366489
DN150	PN25/40	224	169	3	13366417
DN150	PN10/16	218	169	3	13366410
DN200	PN10/16	273	220	3	13366418
DN200	PN25	284	220	3	13366419
DN200	PN40	290	220	3	13366420
DN250	PN10	328	273	1.5	13366455
DN250	PN10	328	273	2	13366491
DN250	PN40	352	273	3	13366424
DN250	PN25	340	273	3	13366423
DN250	PN10	328	273	3	13366421
DN250	PN16	329	273	3	13366422
DN300	PN10	378	324	1.5	13366459
DN300	PN10	378	324	2	13366492
DN300	PN16	384	324	3	13366426
DN300	PN10	378	324	3	13366425
DN300	PN25	400	324	3	13366427

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN300	PN40	417	324	3	13366428
DN350	PN10	438	356	1.5	13366463
DN350	PN10	438	356	2	13366493
DN350	PN16	444	356	3	13366430
DN350	PN40	474	356	3	13366432
DN350	PN25	457	356	3	13366431
DN350	PN10	438	356	3	13366429
DN400	PN10	489	407	1.5	13366467
DN400	PN10	489	407	2	13366494
DN400	PN16	495	407	3	13366434
DN400	PN10	489	407	3	13366433
DN400	PN25	514	407	3	13366435
DN400	PN40	546	407	3	13366436
DN450	PN10	539	458	1.5	13366529
DN450	PN10	539	458	2	13366528
DN450	PN16	555	458	3	13366533
DN450	PN40	571	458	3	13366539
DN450	PN25	564	458	3	13366536
DN450	PN10	539	458	3	13366530
DN500	PN10	594	508	1.5	13366472
DN500	PN10	594	508	2	13366495
DN500	PN10	594	508	3	13366411
DN500	PN25	624	508	3	13366523
DN500	PN40	628	508	3	13366525
DN500	PN16	617	508	3	13366521
DN600	PN10	695	610	1.5	13366473
DN600	PN10	695	610	2	13366496
DN600	PN16	734	610	3	13366522
DN600	PN40	747	610	3	13366526
DN600	PN25	731	610	3	13366524
DN600	PN10	695	610	3	13366520

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.