



LEDUC Balgaccumulator ACS/ACSL

Characteristics

Repairable: No

Max. pressure ratio: 1:4 - 1:8

Type: Bladder accumulator ACSL

Volume l	Connections	Gas connection	Diameter mm	Options	Article
0,7	1/2" BSP	M 28x1.5	108		12590769
0,7	1/2" BSP - M33x1,5	M 28x1.5	108	Precharge = 40 bar	12955589
0,7	1/2" BSP	M 28x1.5	114		12590763
1 1/2	1/2" BSP - M33x1,5	M 28x1.5	108	Precharge = 50 bar	12955588
1 1/2	1/2" BSP	M 28x1.5	108		12590771
1 1/2	3/4" BSP	M 28x1.5	114		12590765
1	1/2" BSP	M 28x1.5	108		12590770
1	3/4" BSP	M 28x1.5	114		12590764
2,5	3/4" BSP	M 28x1.5	108		12590773
2,5	3/4" BSP	M 28x1.5	114		12590767
2	3/4" BSP	M 28x1.5	108		12590772
2	3/4" BSP	M 28x1.5	114		12590766
4	3/4" BSP	M 28x1.5	108		12590774
4	3/4" BSP	M 28x1.5	114		12590768

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.