

Safety clamp coupling for steam steel SHM-HP/EN14423 - male thread



Characteristics

Type: SHM-HP
Type of component: Hose tail coupling
Material: Steel
Connection type: Threaded coupling
Hose fitting type: Male thread
Connection termination: NPT
Elbow angle [degr.]: 0 °
Hose tail execution: Serrated, with safety collar
Temperature range [°C]: -30 / 232 °C

Connection termination size	Hose ID [DN]	Maximum operating pressure		Article
		bar	psi	
1/2		18	261	10070383
3/4"	DN15	18	261	10070386
1/2"	DN15	18	261	10070381
3/4"	DN19	18	261	10039027
1"	DN19	18	261	11024952
1"	DN25	18	261	10070394
1"	DN25	18	261	10070397
1.1/4"	DN32	18	261	10070400
1.1/2"	DN38	18	261	10070406
2"	DN50	18	261	10070412
3/4"	DN19	18	261	10039028
1.1/4"	DN32	18	261	10070403
1.1/2"	DN38	18	261	10070409
2"	DN50	18	261	10070415

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.