


Ball valve Type: 1943R Bronze Flange PN16



Characteristics

Type: 1943R
Norm: EN (DIN)
Construction type: 2-way
Housing construction: 2-part
Housing material: Bronze
Material quality: CC491K EN1982
Connection: Flange
Flange finish: Raised face
Top flange standard: ISO 5211 Direct Mount

Characteristics [2]

Secondary spindle seal material: FPM (FKM)
Tertiary spindle seal material: FPM (FKM)
Body seal: FPM (FKM)
Actuator material: Stainless steel

Nominal inner diameter	Pressure rating	Face to Face norm	Manual operation	Mounting flange	Bore	Material ball	Seat material	Spindle material	Primary spindle seal material	Article
DN15	PN16	EN 558, Series 14	Handle	F04	Full bore	1.4401	PTFE/Graphite	1.4401	PTFE	13389243
DN40	PN16	EN 558, Series 14	Handle	F05	Full bore	1.4401	PTFE/Graphite	1.4401	PTFE	12725791
DN50	PN16	EN 558, Series 14	Handle	F05	Full bore	1.4401	PTFE/Graphite	1.4401	PTFE	12725792
DN80	PN16	EN 558, Series 14	Handle	F07	Full bore	1.4401	PTFE/Graphite	1.4401	PTFE	12725794
DN100	PN16	EN 558, Series 14	Handle	F07	Full bore	1.4401	PTFE/Graphite	1.4401	PTFE	12725784
DN150	PN16	EN 558, Series 14	Handle	F10	Full bore	1.4401	PTFE/Graphite	1.4401	PTFE	12725786
DN200	PN16	EN 558, Series 15	T-wrench	F12	Full bore	1.4401	PTFE/Graphite	1.4401	PTFE	12725788
DN250	PN16	EN 558, Series 14	Bare stem	F12	Full bore	1.4401	PTFE/Graphite	1.4401	PTFE	13395020

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.