



FESTO Activated carbon filter MS6

Characteristics

Series: MS6

Ambient temperature: -10 / 60 °C

Material housing: Aluminium die-cast

Manufacturer ID	Connection	Bowl guard	Flow direction	Maximum flow rate l/min	Ambient temperature °C	Bowl Material	Article
MS6-LFX-1/2-U	G1/2	Integrated	left ? right	900	-10 / 60	Metal	23282857
MS6-LFX-1/2-U-HF	G1/2	Integrated		2500	-10 / 60	Metal	11650975
MS6-LFX-1/2-R-Z	G1/2	Plastic	right ? left	900	-10 / 60	Plastic	11645940
MS6-LFX-1/2-R	G1/2	Plastic	left ? right	900	-10 / 60	Plastic	11645939
MS6-LFX-1/4-U	G1/4	Integrated	left ? right	900	-10 / 60	Metal	11645944
MS6-LFX-1/4-R	G1/4	Plastic	left ? right	900	-10 / 60	Plastic	11645942
MS6-LFX-3/8-R	G3/8	Plastic	left ? right	900	-10 / 60	Plastic	11645946

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.