



FESTO Shut-Off valve HE

Characteristics

Series: HE

Operation: Manual

Fluid: Compressed air in accordance with
ISO8573-1:2010 [7:-:-]

Flow rate at 6 Bar l/min	Port thread type	Port Size in	Port Size mm	Operating pressure bar	Function	Construction size	Housing material	Article
270			QS-6	-0.95 / 10	3/2 bistable	5	PBT-reinforced	23209907
278			QS-6	-0.95 / 10	2/2 bistable	5	PBT-reinforced	23209901
301	BSPT (R)	1/8		-0.95 / 10	3/2 bistable	5	PBT-reinforced	23209909
301	BSPT (R)	1/8		-0.95 / 10	3/2 bistable	5	PBT-reinforced	11630294
307	BSPT (R)	1/8		-0.95 / 10	2/2 bistable	5	PBT-reinforced	11630362
380	BSPT (R)	1/4		-0.95 / 10	3/2 bistable	5	PBT-reinforced	23209910
380	BSPT (R)	1/4		-0.95 / 10	3/2 bistable	7	PBT-reinforced	23210912
388			QS-8	-0.95 / 10	2/2 bistable	5	PBT-reinforced	23209902
390			QS-8	-0.95 / 10	3/2 bistable	5	PBT-reinforced	23209908
396	BSPT (R)	1/4		-0.95 / 10	2/2 bistable	5	PBT-reinforced	23209905
728	BSPT (R)	3/8		-0.95 / 10	2/2 bistable	7	PBT-reinforced	11630363
730	BSPT (R)	3/8		-0.95 / 10	3/2 bistable	7	PBT-reinforced	11630295
733	BSPT (R)	3/8		-0.95 / 10	3/2 bistable	7	PBT-reinforced	11630366
761			QS-10	-0.95 / 10	2/2 bistable	7	PBT-reinforced	23209903
776	BSPT (R)			-0.95 / 10	2/2 bistable	7	PBT-reinforced	23209906
780			QS-10	-0.95 / 10	3/2 bistable	7	PBT-reinforced	11630364
796	BSPT (R)			-0.95 / 10	3/2 bistable	7	PBT-reinforced	11630367
830			QS-12	-0.95 / 10	2/2 bistable	7	PBT-reinforced	23209904
840			QS-12	-0.95 / 10	3/2 bistable	7	PBT-reinforced	11630365

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.