

FESTO Plastic tubing PAN

Characteristics

Series: PAN

Hose material: TPE-A

DIN standard: DIN 73378-PA12-PHL



Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure at 20 °C	Roller length	Colour	Minimum bending radius	Hardness	Weight per meter	Article
mm	mm	mm	bar	m		mm		g	
2.5	0.75	4	31	50	Black	10	D 65 +/-3	8	14169994
2.5	0.75	4	31	500	Black	10	D 65 +/-3	8	14169993
4	1	6	27	50	Black	15	D 65 +/-3	16	12748837
4	1	6	27	500	Black	15	D 65 +/-3	16	14169995
6	1	8	19	50	Black	35	D 65 +/-3	22	12750985
7.5	1.25	10	19	50	Black	45	D 65 +/-3	35	14169996
9	1.5	12	19	50	Black	50	D 65 +/-3	51	14169997
12	2	16	19	50	Black	75	D 65 +/-3	90	14169998
2.9	0.75	4	15	500	Black	12	D 55 +/-3	6	12264529
2.9	0.75	4	15	50	Black	12	D 55 +/-3	6	11651095
2.9	0.75	4	15	50	Blue	12	D 55 +/-3	6	11651087
2.9	0.75	4	15	500	Blue	12	D 55 +/-3	6	12264523
2.9	0.75	4	15	50	Green	12	D 55 +/-3	6	11651097
2.9	0.75	4	15	50	Natural	12	D 55 +/-3	6	11650259
2.9	0.75	4	15	50	Red	12	D 55 +/-3	6	11651099
2.9	0.75	4	15	50	Silver	12	D 55 +/-3	6	23212625
2.9	0.75	4	15	500	Silver	12	D 55 +/-3	6	12264517
2.9	0.75	4	15	50	Yellow	12	D 55 +/-3	6	11651103
4	1	6	19	50	Black	14	D 55 +/-3	16	11651096
4	1	6	19	500	Black	14	D 55 +/-3	16	12264530
4	1	6	19	500	Blue	14	D 55 +/-3	16	12264524
4	1	6	19	50	Blue	14	D 55 +/-3	16	11651088
4	1	6	19	50	Green	14	D 55 +/-3	16	11651098
4	1	6	19	50	Natural	14	D 55 +/-3	16	11650260
4	1	6	19	50	Red	14	D 55 +/-3	16	11651100
4	1	6	19	50	Silver	14	D 55 +/-3	16	23212454
4	1	6	19	500	Silver	14	D 55 +/-3	16	12264518
4	1	6	19	50	Yellow	14	D 55 +/-3	16	11651104
5.9	1.25	8	15	50	Black	22	D 55 +/-3	24	12264535
5.9	1.25	8	15	400	Black	22	D 55 +/-3	24	12264531
5.9	1.25	8	15	400	Blue	22	D 55 +/-3	24	12264525
5.9	1.25	8	15	50	Blue	22	D 55 +/-3	24	11651089
5.9	1.25	8	15	50	Green	22	D 55 +/-3	24	12264539
5.9	1.25	8	15	50	Natural	22	D 55 +/-3	24	11650261
5.9	1.25	8	15	50	Red	22	D 55 +/-3	24	12264543
5.9	1	8	15	50	Silver	22	D 55 +/-3	24	23212626
5.9	1.25	8	15	400	Silver	22	D 55 +/-3	24	12264519
5.9	1.25	8	15	50	Yellow	22	D 55 +/-3	24	12264546
7	1.5	10	17	300	Black	27	D 55 +/-3	42	12264532
7	1.5	10	17	50	Black	27	D 55 +/-3	42	12264536
7	1.5	10	17	50	Blue	27	D 55 +/-3	42	11651092

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure at 20 °C	Roller length	Colour	Minimum bending radius	Hardness	Weight per meter	Article
mm	mm	mm	bar	m		mm		g	
7	1.5	10	17	300	Blue	27	D 55 +/-3	42	12264526
7	1.5	10	17	50	Green	27	D 55 +/-3	42	12264540
7	1.5	10	17	50	Natural	27	D 55 +/-3	42	11650262
7	1.5	10	17	50	Red	27	D 55 +/-3	42	11651101
7	1.5	10	17	50	Silver	27	D 55 +/-3	42	11639080
7	1.5	10	17	300	Silver	27	D 55 +/-3	42	12264520
7	1.5	10	17	50	Yellow	27	D 55 +/-3	42	12264547
8.4	1.75	12	17	50	Black	29	D 55 +/-3	60	12264537
8.4	1.75	12	17	200	Black	29	D 55 +/-3	60	12264533
8.4	1.75	12	17	50	Blue	29	D 55 +/-3	60	11651093
8.4	1.75	12	17	200	Blue	29	D 55 +/-3	60	12264527
8.4	1.75	12	17	50	Green	29	D 55 +/-3	60	12264541
8.4	1.75	12	17	50	Natural	29	D 55 +/-3	60	11650263
8.4	1.75	12	17	50	Red	29	D 55 +/-3	60	12264544
8.4	1.75	12	17	200	Silver	29	D 55 +/-3	60	12264521
8.4	1.75	12	17	50	Silver	29	D 55 +/-3	60	23212627
8.4	1.75	12	17	50	Yellow	29	D 55 +/-3	60	12264548
10	2	14	17	50	Silver	50	D 55 +/-3	77	12266329
12	2	16	14	50	Black	67	D 55 +/-3	92	12264538
12	2	16	14	100	Black	67	D 55 +/-3	92	12264534
12	2	16	14	100	Blue	67	D 55 +/-3	92	12264528
12	2	16	14		Blue	67	D 55 +/-3	92	24212171
12	2	16	14	50	Green	67	D 55 +/-3	92	12264542
12	2	16	14	50	Natural	67	D 55 +/-3	92	11650264
12	2	16	14	50	Red	67	D 55 +/-3	92	12264545
12	2	16	14	100	Silver	67	D 55 +/-3	92	12264522
12	2	16	14	50	Silver	67	D 55 +/-3	92	23212628
12	2	16	14	50	Yellow	67	D 55 +/-3	92	12264549
18	2	22	14		Black	14	D 62 +/-3	1310	14010324
23	2.5	28	14		Black	14	D 62 +/-3	2070	14170038

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.