


FESTO Linear drive DGPL



Characteristics

Series: DGPL

Function: Double acting

Magnetic: Yes

Housing material: Anodised aluminium

Operating temperature: -10 / 60 °C

Manufacturer ID	Cushioning	Bore diameter mm	Stroke length mm	Port Size in	Operating pressure bar	Article
DGPL-25-1000-PPV-A-B-KF	Adjustable	25	1	G1/8	2 / 8	11645107
DGPL-25-250-PPV-A-B-KF	Adjustable	25	250	G1/8	2 / 8	11645104
DGPL-25-400-PPV-A-B-KF	Adjustable	25	400	G1/8	2 / 8	11645105
DGPL-25-500-PPV-A-B-KF	Adjustable	25	500	G1/8	2 / 8	11645106
DGPL-32-1000-PPV-A-B-KF	Adjustable	32	1	G1/8	2 / 8	11645113
DGPL-32-250-PPV-A-B-KF	Adjustable	32	250	G1/8	2 / 8	11645110
DGPL-32-400-PPV-A-B-KF	Adjustable	32	400	G1/8	2 / 8	11645111
DGPL-32-500-PPV-A-B-KF	Adjustable	32	500	G1/8	2 / 8	11645112
DGPL-40-1000-PPV-A-B-KF	Adjustable	40	1	G1/4	1.5 / 8	11645121
DGPL-40-250-PPV-A-B-KF	Adjustable	40	250	G1/4	1.5 / 8	11645118
DGPL-40-400-PPV-A-B-KF	Adjustable	40	400	G1/4	1.5 / 8	11645119
DGPL-40-500-PPV-A-B-KF	Adjustable	40	500	G1/4	1.5 / 8	11645120

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.