



FESTO Membrane air dryer LDM1

Characteristics

- Series:** LDM1
- Temperature range [°C]:** 2 / 50 °C
- Operating pressure:** 3 / 12.5 bar
- Housing material:** Zinc die-casting
- Bowl Material:** Aluminium alloy
- Material seal:** NBR

Outlet air flow rate l/min	Purge air flow rate l/min	Port thread type	Port Size in	Flow direction	With bracket	Article
300	353			left ? right	No	11649950
300	353	Parallel (G)	1/2	left ? right	No	11649953
300	353	Parallel (G)	1	left ? right	No	11649959
300	353	Parallel (G)	3/4	left ? right	No	11649956
600	706			left ? right	No	11649951
600	706	Parallel (G)	1/2	left ? right	No	11649954
600	706	Parallel (G)	1	left ? right	No	11649960
600	706	Parallel (G)	3/4	left ? right	No	11649957
1000	1250			left ? right	No	11649952
1000	1250	Parallel (G)	1/2	left ? right	No	11649955
1000	1250	Parallel (G)	1	left ? right	No	11649961
1000	1250	Parallel (G)	3/4	left ? right	No	11649958

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.