



FESTO Mini slide EGSC

Characteristics

Series: EGSC

Operating temperature: 0 / 50 °C

Degree of protection (IP): 40

Spindle type	Construction size	Stroke length	Spindle pitch	Repetition accuracy	Max. feed force Fx	Article
		mm	mm/U	mm	N	
Ball screw	25	25	6	±0.015	70	14168689
Ball screw	25	50	6	±0.015	70	14168690
Ball screw	25	75	6	±0.015	70	14168691
Ball screw	32	25	8	±0.015	87	14168685
Ball screw	32	50	8	±0.015	87	14168686
Ball screw	32	75	8	±0.015	87	14168687
Ball screw	32	100	8	±0.015	87	14168688
Ball screw	45	25	10	±0.015	188	14168692
Ball screw	45	50	10	±0.015	188	14168693
Ball screw	45	75	10	±0.015	188	14168694
Ball screw	45	100	10	±0.015	188	14168695
Ball screw	45	125	10	±0.015	188	14168696
Ball screw	45	150	10	±0.015	188	14168697
Ball screw	60	50	12	±0.015	345	14168698
Ball screw	60	75	12	±0.015	345	14168699
Ball screw	60	100	12	±0.015	345	14168700
Ball screw	60	125	12	±0.015	345	14168701
Ball screw	60	150	12	±0.015	345	14168702
Ball screw	60	200	12	±0.015	345	14168703

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.