

FESTO Proximity sensor SIEH



Characteristics

Series: SIEH

Standard: EN 60947-5-2

Degree of protection (IP): IP69K

Manufacturer ID	Size	Voltage	Max. switching current	Max. voltage drop	Cable length	Electrical connection	Temperature range	Switching distance	Article
				V			°C	mm	
SIEH-M12B-PO-K-L	M 12	10 - 30 V DC	200	2	2500	Cable	-25 / 70	4	11629896
SIEH-M12B-PS-K-L	M 12	10 - 30 V DC	200	2	2500	Cable	-25 / 70	4	11629893
SIEH-M12B-NS-K-L	M 12	10 - 30 V DC	200	2	2500	Cable	-25 / 70	4	11629891
SIEH-M12B-NO-K-L	M 12	10 - 30 V DC	200	2	2500	Cable	-25 / 70	4	11629894
SIEH-M12B-PS-K-L-CR	M 12	10 - 30 V DC	200	2		Cable, 3-core	-25 / 70	6	11648543
SIEH-M12B-NS-K-L-CR	M 12	10 - 30 V DC	200	2		Cable, 3-core	-25 / 70	6	12263029
SIEH-M12B-NO-S-L	M 12	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	4	11629895
SIEH-M12B-PS-S-L	M 12	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	4	23211363
SIEH-M12B-PO-S-L	M 12	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	4	11629897
SIEH-M12B-NS-S-L	M 12	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	4	11629892
SIEH-M12B-NS-S-L-CR	M 12	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	6	12263028
SIEH-M12B-PS-S-L-CR	M 12	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	6	11648542
SIEH-M18B-PS-K-L	M 18	10 - 30 V DC	200	2	2500	Cable, 3-core	-25 / 70	8	11629900
SIEH-M18B-NS-K-L	M 18	10 - 30 V DC	200	2	2500	Cable, 3-core	-25 / 70	8	11629898
SIEH-M18B-NO-K-L	M 18	10 - 30 V DC	200	2	2500	Cable, 3-core	-25 / 70	8	11629902
SIEH-M18B-PO-K-L	M 18	10 - 30 V DC	200	2	2500	Cable, 3-core	-25 / 70	8	11629904
SIEH-M18B-PS-K-L-CR	M 18	10 - 30 V DC	200	2		Cable, 3-core	-25 / 70	10	11648545
SIEH-M18B-NS-K-L-CR	M 18	10 - 30 V DC	200	2		Cable, 3-core	-25 / 70	10	12263031
SIEH-M18B-PS-S-L	M 18	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	8	11629901
SIEH-M18B-NS-S-L	M 18	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	8	11629899
SIEH-M18B-PO-S-L	M 18	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	8	11629905
SIEH-M18B-NO-S-L	M 18	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	8	11629903
SIEH-M18B-PS-S-L-CR	M 18	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	10	11648544
SIEH-M18B-NS-S-L-CR	M 18	10 - 30 V DC	200	2		Plug, M12x1, 3-pin	-25 / 70	10	12263030
SIEH-3B-PS-S-L	M 12	10 - 30 V DC	100	2	150	Cable with plug, M8x1, 3-pin	-25 / 70	1	11648547
SIEH-3B-NS-S-L	M 12	10 - 30 V DC	100	2	150	Cable with plug, M8x1, 3-pin	-25 / 70	1	11648549
SIEH-3B-NS-K-L	M 12	10 - 30 V DC	100	2	2500	Cable, 3-core	-25 / 70	1	11648550

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Size	Voltage	Max. switching current	Max. voltage drop	Cable length	Electrical connection	Temperature range	Switching distance	Article
				V	mm		°C	mm	
SIEH-3B-PS-K-L	M 12	10 - 30 V DC	100	2	2500	Cable, 3-core	-25 / 70	1	11648548

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.