

FESTO Proximity sensor SIES

Characteristics

Series: SIES

Standard: EN 60947-5-2

Degree of protection (IP): IP67



Manufacturer ID	Size	Voltage	Max. switching current	Max. voltage drop V	Cable length mm	Electrical connection	Temperature range °C	Switching distance mm	Article
SIES-Q8B-NO-K-L									11634225
SIES-Q8B-NO-S-L									11634226
SIES-8M-NO-24V-K-2,5-M8D	Slot 8	10 - 30 V DC	150		2500	Cable with plug, M8x1, 3-pin, turnable threads	-25 / 70	1.5	12264067
SIES-8M-NS-24V-K-5,0-M8D	Slot 8	10 - 30 V DC	150		5000	Cable with plug, M8x1, 3-pin, turnable threads	-25 / 70	1.5	12264063
SIES-8M-PO-24V-K-2,5-M8D	Slot 8	10 - 30 V DC	150		2500	Cable with plug, M8x1, 3-pin, turnable threads	-25 / 70	1.5	12264057
SIES-8M-PS-24V-K-10-M8D	Slot 8	10 - 30 V DC	150		10	Cable with plug, M8x1, 3-pin, turnable threads	-25 / 70	1.5	12264054
SIES-8M-NO-24V-K-5,0-M8D	Slot 8	10 - 30 V DC	150		5000	Cable with plug, M8x1, 3-pin, turnable threads	-25 / 70	1.5	12264068
SIES-8M-NS-24V-K-2,5-M8D	Slot 8	10 - 30 V DC	150		2500	Cable with plug, M8x1, 3-pin, turnable threads	-25 / 70	1.5	12264062
SIES-8M-PO-24V-K-10-M8D	Slot 8	10 - 30 V DC	150		10	Cable with plug, M8x1, 3-pin, turnable threads	-25 / 70	1.5	12264059
SIES-8M-PO-24V-K-0,3-M8D	Slot 8	10 - 30 V DC	150		300	Cable with plug, M8x1, 3-pin, turnable threads	-25 / 70	1.5	12264056
SIES-8M-PS-24V-K-5,0-M8D	Slot 8	10 - 30 V DC	150		5000	Cable with plug, M8x1, 3-pin, turnable threads	-25 / 70	1.5	12264053
SIES-8M-NS-24V-K-0,3-M8D	Slot 8	10 - 30 V DC	150		300	Cable with plug, M8x1, 3-pin, turnable threads	-25 / 70	1.5	12264061
SIES-8M-PS-24V-K-2,5-M8D	Slot 8	10 - 30 V DC	150		2500	Cable with plug, M8x1, 3-pin, turnable threads	-25 / 70	1.5	12264052
SIES-8M-NS-24V-K-10-M8D	Slot 8	10 - 30 V DC	150		10	Cable with plug, M8x1, 3-pin, turnable threads	-25 / 70	1.5	12264064
SIES-8M-PO-24V-K-5,0-M8D	Slot 8	10 - 30 V DC	150		5000	Cable with plug, M8x1, 3-pin, turnable threads	-25 / 70	1.5	12264058

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Size	Voltage	Max. switching current	Max. voltage drop V	Cable length mm	Electrical connection	Temperature range °C	Switching distance mm	Article
SIES-8M-NO-24V-K-10-M8D	Slot 8	10 - 30 V DC	150		10	Cable with plug, M8x1, 3-pin, turnable threads	-25 / 70	1.5	12264069
SIES-8M-NO-24V-K-0,3-M8D	Slot 8	10 - 30 V DC	150		300	Cable with plug, M8x1, 3-pin, turnable threads	-25 / 70	1.5	12264066
SIES-8M-PS-24V-K-0,3-M8D	Slot 8	10 - 30 V DC	150		300	Cable with plug, M8x1, 3-pin, turnable threads	-25 / 70	1.5	24209537
SIES-8M-PO-24V-K-7,5-OE	Slot 8	10 - 30 V DC	150		7500	Cable, 3-core	-25 / 70	1.5	12264055
SIES-8M-NO-24V-K-7,5-OE	Slot 8	10 - 30 V DC	150		7500	Cable, 3-core	-25 / 70	1.5	12264065
SIES-8M-PS-24V-K-7,5-OE	Slot 8	10 - 30 V DC	150		7500	Cable, 3-core	-25 / 70	1.5	12264051
SIES-8M-NS-24V-K-7,5-OE	Slot 8	10 - 30 V DC	150		7500	Cable, 3-core	-25 / 70	1.5	12264060
SIES-Q5B-NO-K-L	5x5x25mm	10 - 30 V DC	200	2	2500	Cable, 3-core	-25 / 70	0.8	11634223
SIES-Q5B-NS-K-L	5x5x25mm	10 - 30 V DC	200	2	2500	Cable, 3-core	-25 / 70	0.8	11634920
SIES-Q5B-PO-K-L	5x5x25mm	10 - 30 V DC	200	2	2500	Cable, 3-core	-25 / 70	0.8	11634224
SIES-Q5B-PS-K-L	5x5x25mm	10 - 30 V DC	200	2	2500	Cable, 3-core	-25 / 70	0.8	11634921
SIES-Q8B-PO-K-L	8x8x40mm	10 - 30 V DC	200	2	2500	Cable, 3-core	-25 / 70	1.5	11634227
SIES-Q8B-PS-K-L	8x8x40mm	10 - 30 V DC	200	2	2500	Cable, 3-core	-25 / 70	1.5	11634924
SIES-Q8B-NS-K-L	8x8x40mm	10 - 30 V DC	200	2	2500	Cable, 3-core	-25 / 70	1.5	11634922
SIES-Q8B-PO-S-L	8x8x59mm	10 - 30 V DC	200	2		Plug, M8x1, 3-pin	-25 / 70	1.5	11634228
SIES-Q8B-PS-S-L	8x8x59mm	10 - 30 V DC	200	2		Plug, M8x1, 3-pin	-25 / 70	1.5	11634925
SIES-Q8B-NS-S-L	8x8x59mm	10 - 30 V DC	200	2		Plug, M8x1, 3-pin	-25 / 70	1.5	11634923
SIES-QB-PO-K-L	12x26x40mm	10 - 30 V DC		3.2	2500	Cable, 3-core	-25 / 85	2	11629932
SIES-QB-PS-K-L	12x26x40mm	10 - 30 V DC		3.2	2500	Cable, M8x1	-25 / 85	2	11629931
SIES-V3B-NS-S-L	15x20x30mm	10 - 30 V DC		3.2		Plug, M8x1, 3-pin	-25 / 85	2	11629933
SIES-V3B-PS-S-L	15x20x30mm	10 - 30 V DC		3.2		Plug, M8x1, 3-pin	-25 / 85	2	11629934
SIES-Q40B-PAX-2L	40x40x120mm	10 - 30 V DC		3.5		Screwed terminal	-25 / 85	15	11629935

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.