

FESTO Parallel gripper HGPL

Characteristics

Series: HGPL

Operating temperature: 5 / 60 °C



Manufacturer ID	Bore diameter mm	Operation	Stroke length mm	Connection	Total force at 6 bar, closing N	Total force at 6 bar, opening N	Operating pressure bar	Article
HGPL-14-80-A-B	14	Double acting	80	M5	158	126	3 / 8	13208437
HGPL-14-60-A-B	14	Double acting	60	M5	158	126	3 / 8	13208436
HGPL-14-40-A-B	14	Double acting	40	M5	158	126	3 / 8	13208435
HGPL-14-20-A-B	14	Double acting	20	M5	158	126	3 / 8	13208434
HGPL-25-20-A-B	25	Double acting	20	M5	512	412	3 / 8	13208438
HGPL-25-80-A-B	25	Double acting	80	M5	512	412	3 / 8	13208441
HGPL-25-40-A-B	25	Double acting	40	M5	512	412	3 / 8	13208439
HGPL-25-60-A-B	25	Double acting	60	M5	512	412	3 / 8	13208440
HGPL-40-40-A-B	40	Double acting	40	M5	1.216	1.038	3 / 8	13208444
HGPL-40-100-A-B	40	Double acting	100	M5	1.216	1.038	3 / 8	13208448
HGPL-40-60-A-B	40	Double acting	60	M5	1.216	1.038	3 / 8	13208445
HGPL-40-20-A-B	40	Double acting	20	M5	1.216	1.038	3 / 8	13208443
HGPL-40-80-A-B	40	Double acting	80	M5	1.216	1.038	3 / 8	13208446
HGPL-63-150-A-B	63	Double acting	150	G1/8	2.742	2.466	3 / 8	13208452
HGPL-63-60-A-B	63	Double acting	60	G1/8	2.742	2.466	3 / 8	13208450
HGPL-63-100-A-B	63	Double acting	100	G1/8	2.742	2.466	3 / 8	13208451

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.