



FESTO Parallel gripper HGPP

Characteristics

Series: HGPP

Operating temperature: 5 / 60 °C

Manufacturer ID	Bore diameter mm	Operation	Stroke length mm	Connection	Total force at 6 bar, closing N	Total force at 6 bar, opening N	Operating pressure bar	Article
HGPP-10-A-G2	10	Double acting	2	M3			5 / 8	11644831
HGPP-10-A	10	Double acting	2	M3	80	80	2 / 8	11644829
HGPP-10-A-G1	10	Double acting	2	M3			5 / 8	11644830
HGPP-12-A-G2	12	Double acting	2.5	M3			5 / 8	11635925
HGPP-12-A-G1	12	Double acting	2.5	M3			5 / 8	11635924
HGPP-12-A	12	Double acting	2.5	M3	116	116	2 / 8	23211808
HGPP-16-A	16	Double acting	5	M5	204	204	2 / 8	11635926
HGPP-16-A-G2	16	Double acting	5	M5			5 / 8	11635928
HGPP-16-A-G1	16	Double acting	5	M5			5 / 8	11635927
HGPP-20-A-G1	20	Double acting	7.5	M5			5 / 8	11635930
HGPP-20-A-G2	20	Double acting	7.5	M5			5 / 8	11635931
HGPP-20-A	20	Double acting	7.5	M5	340	340	2 / 8	11635929
HGPP-25-A-G2	25	Double acting	10	M5			5 / 8	11644834
HGPP-25-A-G1	25	Double acting	10	M5			5 / 8	11644833
HGPP-25-A	25	Double acting	10	M5	500	500	2 / 8	11644832
HGPP-32-A-G1	32	Double acting	12.5	G1/8			5 / 8	11644836
HGPP-32-A-G2	32	Double acting	12.5	G1/8			5 / 8	11644837
HGPP-32-A	32	Double acting	12.5	G1/8	830	830	2 / 8	11644835

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.