



## FESTO Precision pressure regulator MS6-LRP

### Characteristics

**Series:** MS6-LRP

**Flow rate:** >= 800 l/min

**Material seal:** NBR

**Material housing:** Aluminium

**Temperature range [°C]:** -10 / 60 °C

| Pressure range<br>bar | Operating pressure<br>bar | Weight<br>g | Article  |
|-----------------------|---------------------------|-------------|----------|
| 0.05 / 2.5            | 1 / 14                    | 1000        | 11648453 |
| 0.1 / 4               | 1 / 14                    | 1000        | 11648455 |
| 0.5 / 12              | 1 / 14                    | 1000        | 11648458 |
| 0.5 / 12              | 1 / 14                    | 1000        | 11648457 |
| 0.05 / 7              | 1 / 14                    | 1000        | 11648451 |
| 0.05 / 7              | 1 / 14                    | 1000        | 11648459 |
| 0.05 / 2.5            | 1 / 14                    | 1000        | 11648461 |
| 0.1 / 4               | 1 / 14                    | 1000        | 11648463 |
| 0.5 / 12              | 1 / 14                    | 1000        | 11648465 |
| 0.05 / 7              | 1 / 14                    | 1000        | 11648467 |
| 0.05 / 2.5            | 1 / 14                    | 1000        | 11648470 |
| 0.05 / 2.5            | 1 / 14                    | 1000        | 11648469 |
| 0.1 / 4               | 1 / 14                    | 1000        | 11648471 |
| 0.5 / 12              | 1 / 14                    | 1000        | 11648473 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.