



FESTO Reducing sleeve NPFC-R

Characteristics

Series: NPFC-R

Ambient temperature: -20 / 150 °C

Operating pressure: -0.95 / 50 bar

Manufacturer ID	Material	Threaded connection 1	Connection 1 thread size	Threaded connection 2	Connection 2 thread size	Article
NPFC-R-G12-G14-F	Brass, Nickel-plated	Internal thread BSPP (G)	1/2	Internal thread BSPP (G)	1/4	13500475
NPFC-R-G12-G18-F	Brass, Nickel-plated	Internal thread BSPP (G)	1/2	Internal thread BSPP (G)	1/8	14169527
NPFC-R-G14-G18-F	Brass, Nickel-plated	Internal thread BSPP (G)	1/4	Internal thread BSPP (G)	1/8	14045466
NPFC-R-G1-G12-F	Brass, Nickel-plated	Internal thread BSPP (G)	1	Internal thread BSPP (G)	1/2	14169528
NPFC-R-G1-G34-F	Brass, Nickel-plated	Internal thread BSPP (G)	1	Internal thread BSPP (G)	3/4	14169529
NPFC-R-G34-G12-F	Brass, Nickel-plated	Internal thread BSPP (G)	3/4	Internal thread BSPP (G)	1/2	12639401
NPFC-R-G38-G18-F	Brass, Nickel-plated	Internal thread BSPP (G)	3/8	Internal thread BSPP (G)	1/8	12639393

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.