


FESTO Toothed belt axis ELGA



Characteristics

Series: ELGA

Operating temperature: -10 / 60 °C

Degree of protection (IP): 40

Construction size	Stroke length	Repetition accuracy	Max. feed force Fx	Article
	mm	mm	N	
70	300	±0.08	350	14170405
70	400	±0.08	350	14170407
70	500	±0.08	350	13252244
70	600	±0.08	350	14170410
70	800	±0.08	350	14170412
70	1000	±0.08	350	14170415
70	1200	±0.08	350	14170418
80	400	±0.08	800	14170414
80	500	±0.08	800	13671189
80	600	±0.08	800	14170416
80	800	±0.08	800	14170419
80	1000	±0.08	800	14170422
80	1200	±0.08	800	14170424
120	400	±0.08	1300	14170427
120	500	±0.08	1300	14170428
120	600	±0.08	1300	14170429
120	800	±0.08	1300	14170431
120	1000	±0.08	1300	14170432
120	1200	±0.08	1300	14170433
120	1500	±0.08	1300	14170434

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.