


FESTO Toothed belt axis ELGC



Characteristics

Series: ELGC

Operating temperature: 0 / 50 °C

Degree of protection (IP): 40

Construction size	Stroke length	Repetition accuracy	Max. feed force Fx	Article
	mm	mm	N	
45	200	±0.1	75	14170347
45	300	±0.1	75	14170351
45	500	±0.1	75	14170361
45	600	±0.1	75	14170363
45	800	±0.1	75	14170371
45	1000	±0.1	75	14170377
45	1200	±0.1	75	14170380
45	1500	±0.1	75	14170386
60	200	±0.1	120	14170350
60	300	±0.1	120	14170355
60	500	±0.1	120	14170364
60	600	±0.1	120	14170368
60	800	±0.1	120	14170375
60	1000	±0.1	120	14170382
60	1200	±0.1	120	14170385
60	1500	±0.1	120	14170389
60	1800	±0.1	120	14170392
60	2000	±0.1	120	14170394
80	200	±0.1	250	14170353
80	300	±0.1	250	14170359
80	500	±0.1	250	14170367
80	600	±0.1	250	14170372
80	800	±0.1	250	14170379
80	1000	±0.1	250	14170383
80	1200	±0.1	250	14170388
80	1500	±0.1	250	14170391
80	1800	±0.1	250	14170395
80	2000	±0.1	250	14170396

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.