

FESTO Distributor block FR



Characteristics

Series: FR

Primary thread size in	Secondary connection	Secondary thread size in	Material	Max. operating pressure bar	Temperature °C	Article
G1/8		G1/8	Aluminium die-cast	16	-10 / 80	23212438
G1/8		M5	Aluminum anodized	16	-10 / 60	23212530
G1/8		M3	Aluminum anodized	16	-10 / 80	11627862
G1/4		G1/4	Aluminium die-cast	16	-10 / 80	23212526
G1/4		G1/4	Aluminum anodized	16	-10 / 80	23212904
G1/4	4mm		Aluminium die-cast	8	-10 / 60	11626808
G1/4	6mm		Aluminium die-cast	8	-10 / 60	11626809
G3/8		G1/8	Aluminium die-cast	16	-10 / 60	23212462
G3/8		G3/8	Aluminium die-cast	16	-10 / 80	11402208
G1/2		G1/4	Aluminium die-cast	16	-10 / 60	23212528
G1/2		G1/2	Aluminium die-cast	16	-10 / 80	23212527
G3/4		G1/2	Aluminium die-cast	16	-10 / 60	23212529

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.