



FESTO Semi-Rotary drive DSM

Characteristics

Series: DSM

Function: Double acting

Housing material: Wrought aluminium alloy,
anodized

Operating temperature: 0 / 60 °C

Manufacturer ID	Cushioning	Construction size	Port Size mm	Port Size in	Operating pressure bar	Article
DSM-32-270-HD-A-B		32		G1/8		13447991
DSM-6-180-P-FW	Mechanical	6	M 3		3.5 / 8	11635402
DSM-6-180-P-FF-FW	Mechanical	6	M 3		3.5 / 8	11635405
DSM-6-90-P-A-FW	Mechanical	6	M 3		3.5 / 8	11635403
DSM-6-90-P	Mechanical	6	M 3		3.5 / 8	11633803
DSM-6-180-P-A	Mechanical	6	M 3		3.5 / 8	11633811
DSM-6-180-P-A-FF-FW	Mechanical	6	M 3		3.5 / 8	11635406
DSM-6-90-P-FW	Mechanical	6	M 3		3.5 / 8	11635401
DSM-6-180-P-A-FF	Mechanical	6	M 3		3.5 / 8	11634548
DSM-6-180-P	Mechanical	6	M 3		3.5 / 8	11633804
DSM-6-180-P-A-FW	Mechanical	6	M 3		3.5 / 8	11635404
DSM-6-90-P-A	Mechanical	6	M 3		3.5 / 8	11633810
DSM-6-180-P-FF	Mechanical	6	M 3		3.5 / 8	11634545
DSM-T-6-180-P	Mechanical	6	M 3		4 / 8	12576089
DSM-T-6-180-P-FW	Mechanical	6	M 3		4 / 8	12576090
DSM-T-6-90-P	Mechanical	6	M 3		4 / 8	12576091
DSM-T-6-90-P-FW	Mechanical	6	M 3		4 / 8	12576093
DSM-8-180-P-A	Mechanical	8	M 3		3.5 / 8	11633813
DSM-T-8-90-P-FW	Mechanical	8	M 3		4 / 8	12576099
DSM-8-90-P-FW	Mechanical	8	M 3		3.5 / 8	11635407
DSM-T-8-180-P-FW	Mechanical	8	M 3		4 / 8	12576096
DSM-T-8-90-P	Mechanical	8	M 3		4 / 8	12576098
DSM-T-8-180-P	Mechanical	8	M 3		4 / 8	12576095
DSM-8-180-P-A-FW	Mechanical	8	M 3		3.5 / 8	11635410
DSM-8-180-P-A-FF-FW	Mechanical	8	M 3		3.5 / 8	11635412
DSM-8-180-P-FF-FW	Mechanical	8	M 3		3.5 / 8	11635411
DSM-8-90-P-A	Mechanical	8	M 3		3.5 / 8	11633812
DSM-8-180-P	Mechanical	8	M 3		3.5 / 8	11633806
DSM-8-90-P-A-FW	Mechanical	8	M 3		3.5 / 8	11635409
DSM-8-90-P	Mechanical	8	M 3		3.5 / 8	11633805
DSM-8-180-P-A-FF	Mechanical	8	M 3		3.5 / 8	11634549
DSM-8-180-P-FW	Mechanical	8	M 3		3.5 / 8	11635408
DSM-8-180-P-FF	Mechanical	8	M 3		3.5 / 8	11634546
DSM-10-240-P-A-FF-FW	Mechanical	10	M 3		2.5 / 8	11635419
DSM-10-240-P-A	Mechanical	10	M 3		2.5 / 8	11633816
DSM-10-240-P-A-FW	Mechanical	10	M 3		2.5 / 8	11635417
DSM-10-90-P-A	Mechanical	10	M 3		2.5 / 8	11633814
DSM-10-180-P-FW	Mechanical	10	M 3		2.5 / 8	11635414
DSM-10-90-P-A-FW	Mechanical	10	M 3		2.5 / 8	23211206
DSM-10-240-P-A-FF	Mechanical	10	M 3		2.5 / 8	11634550
DSM-10-240-P-FF	Mechanical	10	M 3		2.5 / 8	11634547
DSM-10-240-P	Mechanical	10	M 3		2.5 / 8	11633809
DSM-10-240-P-FW	Mechanical	10	M 3		2.5 / 8	11635415

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Cushioning	Construction size	Port Size mm	Port Size in	Operating pressure bar	Article
DSM-10-180-P-A-FW	Mechanical	10	M 3		2.5 / 8	11635416
DSM-10-180-P	Mechanical	10	M 3		2.5 / 8	11633808
DSM-10-240-P-FF-FW	Mechanical	10	M 3		2.5 / 8	11635418
DSM-10-180-P-A	Mechanical	10	M 3		2.5 / 8	11633815
DSM-10-90-P	Mechanical	10	M 3		2.5 / 8	11633807
DSM-10-90-P-FW	Mechanical	10	M 3		2.5 / 8	11635413
DSM-T-10-90-P	Mechanical	10	M 3		3.5 / 8	12576086
DSM-T-10-180-P-FW	Mechanical	10	M 3		3.5 / 8	12576081
DSM-T-10-180-P	Mechanical	10	M 3		3.5 / 8	12576080
DSM-T-10-90-P-FW	Mechanical	10	M 3		3.5 / 8	12576088
DSM-T-10-240-P-FW	Mechanical	10	M 3		3.5 / 8	12576085
DSM-T-10-240-P	Mechanical	10	M 3		3.5 / 8	12576083

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.