

MOBREY Float switch fig. 8390 aluminium horizontal square A type flange



Characteristics

Series: S190

Type: 8390

Process connection: Flange

Contact version: Silver

Switching power: 440V / 5A / 2000VA AC - 240V / 1A
/ 35W DC inductive - 240V / 1A / 35W DC resistive

Switching range: 120 mm

Housing material: Aluminium

Material wet portion housing: Stainless steel 316

Characteristics [2]

Float material: Stainless steel 316

Material cover: Aluminium alloy


Material of connection: Stainless steel 316

With sleeve: Yes

Level of protection (IP value): IP66

Ambient temperature: -30 / 70 °C

Explosion-proof: No



uitvoering met FB4 vlotter

Model	Mounting	Size process connection	Max. operating pressure bar	Min. specific density of liquid kg/m ³	Float diameter mm	Contact type	Adjustable differential gap	Switching differential	Switch point L1 mm	Article
Horizontal float switch	Horizontal	Square A	0	750	65	1 x NO en 1 x NC	No	13 mm	60	13461085
Horizontal float switch	Horizontal	Square A	0	750	65	2 change-over contacts	No	13 mm		13461086

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.