


ECON® Needle valve fig. 719 brass angle pattern internal thread BSP



Characteristics

Type: 719
Norm: EN (DIN)
Construction type: Angle Pattern
Housing material: Brass
Material quality: CW614N
Connection: Internal thread (BSPP)
Face to Face norm: Manufacturer standard
Spindle material: CW614N

Characteristics [2]

Primary spindle seal material: PTFE
Actuator material: Plastic
Minimum medium temperature (continuous): -10 °C
Maximum medium temperature (continuous): 150 °C

Thread connection ["]	d mm	L1 mm	L2 mm	H (open) mm	M mm
1/4	4	23	21.5	80	50
1/2	6	30	17.5	92	65

Max. oper. press.	Max. medium temperature
100 bar	30°C
40 bar	150°C

Nominal inner diameter	Pressure rating	Face to Face length mm	Operation	Valve bore mm	Maximum pressure difference at 20 °C bar	Article
1/4" [8]	PN100	23	Hand wheel	4	100	13221976
1/2" [15]	PN100	30	Hand wheel	6	100	13417613

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.