



ECON® Check valve fig. 1109 steel flange



Characteristics

Type: 1109
Norm: EN (DIN)
Construction type: Straight
Surface protection: Standard manufacturers coating
Connection: Flange
Flange finish: Raised face
Material cover: 1.0619+N
Material jointed arm: 1.0619+N

Characteristics [2]

Minimum medium temperature (continuous): -20 °C
Maximum medium temperature (continuous): 400 °C
Maximum pressure at 20 C: 40 bar

Housing material	Material quality	Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face norm	Face to Face lenght	Valve shape	Sealing	Valve material	Article	
						mm					
Steel	1.0619+N	DN50	PN40	PN40	EN 558, Serie 1	230	Swing type	1.4021	1.0619+N	13496642	
Steel	1.0619+N	DN65	PN40	PN40	EN 558, Serie 1	290	Swing type	1.4021	1.0619+N	13496643	
Steel	1.0619+N	DN80	PN40	PN40	EN 558, Serie 1	310	Swing type	1.4021	1.0619+N	13496644	
Steel	1.0619+N	DN100	PN40	PN40	EN 558, Serie 1	350	Swing type	1.4021	1.0619+N	13496645	
Steel	1.0619+N	DN125	PN40	PN40	EN 558, Serie 1	400	Swing type	1.4021	1.0619+N	13496646	
Steel	1.0619+N	DN150	PN40	PN40	EN 558, Serie 1	480	Swing type	1.4021	1.0619+N	13496647	
Steel	1.0619+N	DN200	PN40	PN40	EN 558, Serie 1	600	Swing type	1.4021	1.0619+N	13496648	
Steel	1.0619+N	DN250	PN40	PN40	EN 558, Serie 1	730	Swing type	1.4021	1.0619+N	13496649	

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.