

AFLEX Hose Bioflex Ultra, smooth bore PTFE hose



Application

- very flexible PTFE suction and delivery hose for high loads
- suitable for the pharmaceutical industry and food industry
- the unique patented design makes the hose smooth on the inside, very flexible, virtually kink-resistant and easy to clean
- it can be installed in confined spaces, as the flow is guaranteed even with a very small bending radius
- the design ensures a higher flow rate and a lower pressure drop than with a corrugated PTFE hose
- for environments where hygiene is important, the hose is available with an outer cover made of food-safe rubber
- Recommended in: Food & Beverages, Pharma

Technical Information

Temperature range

- -73 °C to +260 °C
- for autoclave cleaning, a maximum temperature of 135 °C applies for at least 300 x 30 minutes

Burst pressure

- safety factor 4:1

Test pressure

- 1.5 x maximum operating pressure

Vacuum resistance*

- 90% to 200 °C
- *) to 200 °C; At temperatures > 200 °C, the vacuum resistance decreases by 2% for every 1°C that the temperature increases.

Construction

Inner wall

- white PTFE
- smooth, seamless inner wall, phthalate-free
- "rib" profile on the outside

Reinforcement

- stainless steel spiral AISI 316

Outer cover

- stainless steel braiding AISI 316

Execution

Couplings

- PTFE crimping or hydraulically and hygienically pressed

Approval

Standards/approvals

- EC1935/2004 - EU 10/2011 A,B,C,D1,D2,E
- FDA 21 CFR 177.1550
- USP VI
- 3A for the PTFE base material


Options

Other versions

- Bioflex Ultra PB: white PTFE with PP braiding (up to 100 °C)
- Bioflex Ultra RC: white PTFE with blue EPDM coating (up to 150 °C)
- Bioflex Ultra SI: white PTFE with transparent or semi-transparent silicone coating (up to 204 °C)
- Bioflex Ultra BK: white PTFE with black, antistatic, fire-resistant EPDM coating (up to 150 °C)

Options

- image is for illustration purposes only
- hoses with Hastelloy braiding available on request
- hoses in antistatic design (black PTFE) available on request
- available with full-length stainless-steel protective spiral
- pressure test report
- clearly visible laser engraving on rotatable sleeve



Description	Article
Slang webshop Bioflex Ultra DN25 2xP/W	13175429
Slang webshop Bioflex Ultra DN25 2xTC	13175430

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.