SYSTEM PLAST Split sprockets square bore floating for chains 2500RR

Characteristics

Type: Drive sprocket

Manufacturer ID	Pitch mm	Pitch in	Bore mm	Number of teeth	Execution	Material mm	Article
2500-12S40M-DMS	50.8	2	40	12	Floating	Polyamide	12663181
2500-10S60M-DMS	50.8	2	60	10	Floating	Polyamide	12663182
2500-12S60M-DMS	50.8	2	60	12	Floating	Polyamide	13679735
2500-13S60M-DMS	50.8	2	60	13	Floating	Polyamide	13679741
2500-14S60M-DMS	50.8	2	60	14	Floating	Polyamide	13679748
2500-15S60M-DMS	50.8	2	60	15	Floating	Polyamide	13679755
2500-10S65M-DMS	50.8	2	65	10	Floating	Polyamide	13679730
2500-12S65M-DMS	50.8	2	65	12	Floating	Polyamide	13679737
2500-13S65M-DMS	50.8	2	65	13	Floating	Polyamide	13679744
2500-14S65M-DMS	50.8	2	65	14	Floating	Polyamide	13679751
2500-15S65M-DMS	50.8	2	65	15	Floating	Polyamide	13679757
2500-12S90M-DMS	50.8	2	90	12	Floating	Polyamide	13679739
2500-13S90M-DMS	50.8	2	90	13	Floating	Polyamide	13679746
2500-14S90M-DMS	50.8	2	90	14	Floating	Polyamide	13679753

PR5068226142536899_EN_19.05.2024

ERIKS BV | Tel: +31 88 855 82 33 | E-mail: openaandrijvingen@eriks.nl