



ASCO Solenoid valve 2/2 Type: 32604 series 222 brass internal thread

Characteristics

Series: 222

Type: 32604

Function: Normally closed (NC)

Actuation: Indirect-acting

Electrical connection: Plug EN 175301-803 type A

Housing material: Brass

Sealing: EPDM

Material coil housing: Epoxy

Material shorting ring: Copper

Membrane material: PTFE

Working time: 100 %

Level of protection (IP value): IP65

Emergency manual operation: None

Explosion-proof: No

Medium temperature: From 0 °C to 165 °C


Ambient temperature: From -20 °C to 40 °C

Application

- Steam.Hot water.

Technical Information

- Deactivated when closed.



Size process connection	Process connection	Orifice	Kvs value	Minimum pressure difference	Maximum pressure difference	Coil type	Supply voltage	Power	Starting power	Article
		mm	m³/h	bar	bar					
1/2" (15)	Internal thread (BSPP)	9.5	2.2	0.07	6	400325-117	230V AC	6 W / 15.6 VA	34 VA	11395753

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.