

ECON® Level indicator magnetic fig. 7190 stainless steel flange

Characteristics

Type: 7190

Model: 2 Side connections

Process connection: Flange

Size process connection: DN25

Pressure rating flange: PN40

Maximum pressure at 20 °C: 40 bar

Medium temperature: 0 / 160 °C

Min. specific density of liquid: 920 kg/m³

Max. specific density of liquid: 1.075 kg/m³

Max. viscosity: 500

Housing material: Stainless steel [1.4404]

Material indication rail: Aluminium

Sealing: Graphite

Vent: Plug 1/2" BSPP external thread

Drain: Plug 1/2" BSPP external thread

Number of switches: 0

Pointers: Yes

Approval

Optional:

- Explosion proof according ATEX II 1/2G Ex h EEC T6-T1 Ga/Gb.
- Explosion proof according ATEX IIID Ex h IIIC T85 °C ... T450 °C Da.
- Maritime approval according Lloyds Register or Bureau Veritas.

Options

- Other Flange connection according DIN or ASME
- End switches for alarm or control
- Analog output 4-20mA with reedchain
- Scale available in centimeters [cm], percentage [%] or litres [l]
- Low temperature model


Application

- Indication of liquid levels on vessels and systems.

Technical Information

- Closed design.
- In combination with magnetic switches, alarms and switching can be integrated.

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

**Pointer D****Size table:**

Centre-to-centre distance	Float leakage Indication	A	B	C	H
mm		mm	mm	mm	mm
500	No	220	73	100	500
500	Yes	270	73	100	500
1000	No	220	73	100	1000
1000	Yes	270	73	100	1000
1500	Yes	270	73	100	1500
1500	No	220	73	100	1500
2000	No	220	73	100	2000
2000	Yes	270	73	100	2000
2500	Yes	270	73	100	2500
2500	No	220	73	100	2500

Centre-to-centre distance	Float leakage Indication	Drainage length	Article
mm		mm	
500	No	220	13684906
500	Yes	270	12725855
1000	No	220	13684907
1000	Yes	270	12725851
1500	Yes	270	12725852
1500	No	220	13684908
2000	No	220	13684909
2000	Yes	270	12725853
2500	Yes	270	12725854
2500	No	220	13684910

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.