



R + L Lantern piece / cooler type KPV

Characteristics

Type: Bellhousing for pump with SAE flange

With pump: Pump with SAE flange

Material: Aluminium

Suitable for pumps	Suitable for motor drive	Options	Article
SAE-A flange [PVM/V10]	11,0 kW 4p [1500] Ø350 mm Size 160M	Integrated cooler	12551246
SAE-A flange [V10/PVQ]	2,20 - 4,00 kW 4p [1500] Ø250 mm Size 100L/112M	Integrated cooler	12551241
SAE-A flange [V10/PVQ/PVM]	5,50 - 7,50 kW 4p [1500] Ø300 mm Size 132S/M	Integrated cooler	12551242
SAE-A flange [V10]	1,10 - 1,50 kW 4p [1500] Ø200 mm Size 90S/L	Integrated cooler	12551240
SAE-A flange [V20]	11,0 - 15,0 kW 4p [1500] Ø350 mm Size 160M/L	Integrated cooler	12551239
SAE-B flange [20V(Q)]	7,50 kW 4p [1500] Ø300 mm Size 132/M	Integrated cooler	12551243
SAE-B flange [PVM]	11,0 - 15,0 kW 4p [1500] Ø350 mm Size 160M/L	Integrated cooler	12573076
SAE-B flange [PVM/420/20V(Q)]	18,5 - 22,0 kW 4p [1500] Ø350 mm Size 180M/L	Integrated cooler	12551244
SAE-C flange [PVM]	15,0 kW 4p [1500] Ø350 mm Size 160L	Integrated cooler	12573077
SAE-C flange [PVM/420]	18,5 - 22,0 kW 4p [1500] Ø350 mm Size 180M/L	Integrated cooler	12551245

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.