

R + L Flexible coupling type Spidex



Characteristics

Type: Drive coupling for pump SAE flange

With pump: Pump with SAE flange

Material: Sintered steel

Suitable for pumps	Suitable for motor drive	Article
SAE-A flange straight shaft 3/4" [PVQ/PVM/V10]	5,50 kW 4p [1500] Ø38 mm Size 132S	12551220
SAE-A flange straight shaft 3/4" [V10]	2,20 - 4,00 kW 4p [1500] Ø28 mm Size 100L/112M	12551219
SAE-A flange straight shaft 3/4" [V10]	7,50 kW 4p [1500] Ø38 mm Size 132M	12551392
SAE-A flange straight shaft 5/8" [PVM]	7,50 kW 4p [1500] Ø38 mm Size 132M	12551222
SAE-B flange splined shaft 15T [420]	18,5 - 22,0 kW 4p [1500] Ø48 mm Size 180M/L	12551236
SAE-B flange splined shaft 15T [420]	30,0 kW 4p [1500] Ø55 mm Size 200L	12551237
SAE-B flange straight shaft 7/8" [20V[Q]]	7,50 kW 4p [1500] Ø38 mm Size 132M	12551387
SAE-B flange straight shaft 7/8" [PVM]	15,0 kW 4p [1500] Ø42 mm Size 160L	12573079
SAE-C flange straight shaft 1.1/2" [PVM]	37,0 - 45,0 kW 4p [1500] Ø60 mm Size 225S/M	12551231
SAE-C flange straight shaft 1.1/2" [PVM]	55,0 kW 4p [1500] Ø65 mm Size 250M	12551233
SAE-C flange straight shaft 1.1/4" [PVM]	18,5 - 22,0 kW 4p [1500] Ø48 mm Size 180M/L	12551226
SAE-C flange straight shaft 1.1/4" [PVM]	30,0 kW 4p [1500] Ø55 mm Size 200L	12551225

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.