FESTO Proximity sensor SMEO-1



Characteristics

Series: SMEO-1 Construction type housing: Block Measurement principle: Reed magnetic

Manufacturer ID	Operating voltage at DC V	Type of switching output	Type of switch function	Electrical connection	Article
SMEO-1-B	0 / 200	with contact, bipolar	Normally open contact (NO)	Cable, 2-core	23210169
SMEO-1-LED-230-B	0 / 200	with contact, bipolar	Normally open contact (NO)	Cable, 2-core	23210214
SMEO-1-LED-230-K5-B	0 / 200	with contact, bipolar	Normally open contact (NO)	Cable, 2-core	11631685
SMEO-1-S6-C	0 / 200	with contact, bipolar	Normally open contact (NO)	Cable, 2-core	23210213
SMEO-1-LED-24-K5-B	12 / 27	with contact, bipolar	Normally open contact (NO)	Cable, 3-core	23209736
SMEO-1-LED-24-B	12 / 27	with contact, bipolar	Normally open contact (NO)	Cable, 3-core	23209727
SMEO-1-S-LED-24-B	12 / 27	with contact, bipolar	Normally open contact (NO)	Plug, M8x1, 3-pin	23210215
SMEO-1-S-24-B	0 / 30	with contact, bipolar	Normally open contact (NO)	Plug, M8x1, 3-pin	23210680

PR653460392136410_EN_19.05.2024

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

