



ERIKS Ring Spacer DIN

Ring Spacers are often permanently mounted in the piping system (as spacer). The advantage is that during work- or turnaround periods these Ring Spacers can be exchanged for (pressure) spades. Ring Spacers are also called spacers or spade flanges.

Characteristics

Material: Steel

Material quality: P265-GH

Handle marking: Size, pressure class, material, thickness, marking 'SPACER' and batch number

Surface treatment: smooth finish (RA value 3,2-6,3) on sealing surface on both sides

Size table:

A	C	D	E	T
mm	mm	mm	mm	mm
46	117		25	5
51	114.5		25	5
61	119.5		25	5
71	119.5		25	5
82	124		40	5
92	129		40	6
107	131.5	18	40	8
127	141.5	18	40	8
142	139	18	40	12
162	149	18	60	12
168	146	22	60	12
192	149	18	60	12
194	148	26	60	12
218	161	22	75	14
224	158	26	75	18
273	173.5	22	75	11
273	173.5	22	75	14
284	168	26	75	17
290	165	30	75	22
328	181	22	75	13
329	180.5	26	75	16
340	175	30	75	21
352	169	33	75	27
378	201	22	75	15
384	198	26	75	18

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Size table:

A	C	D	E	T
400	190	30	80	24
417	181.5	33	80	31
438	201	22	75	16
444	198	26	75	21
457	191.5	33	80	27
474	183	36	80	35
489	215.5	26	75	18
495	212.5	30	75	23
514	203	36	80	30
546	187	39	80	40
539	190.5	26	75	20
555	182.5	30	75	26
564	178	36	80	32
571	174.5	39	80	41
594	223	26	75	22
617	211.5	33	75	28
624	208	36	80	36
628	206	42	80	45
695	223	30	75	25
734	211.5	36	80	33
731	208	39	80	41
747	206	48	100	53

Flange compression stage (PN)	Diameter bolt circle	Type of handle	Weight	A	C	D	E	T	Article
	mm		kg	mm	mm	mm	mm	mm	
10/40		Type 1	0.15	46	117		25	5	13460513
10/40		Type 1	0.15	51	114.5		25	5	13460514
10/40		Type 1	0.21	61	119.5		25	5	13460515
10/40		Type 1	0.28	71	119.5		25	5	13460516
10/40		Type 1	0.38	82	124		40	5	13460517
10/40		Type 1	0.47	92	129		40	6	13460518
10/40	125	Type 2	0.61	107	131.5	18	40	8	13460519
10/40	145	Type 2	0.83	127	141.5	18	40	8	13460520
10/40	160	Type 2	1.01	142	139	18	40	12	13460521
10/16	180	Type 2	1.5	162	149	18	60	12	13460510
25/40	190	Type 2	1.5	168	146	22	60	12	13460538
10/16	210	Type 2	2.71	192	149	18	60	12	13460511
25/40	220	Type 2	2.71	194	148	26	60	12	13460539
10/16	240	Type 2	3.35	218	161	22	75	14	13460512
25/40	250	Type 2	3.35	224	158	26	75	18	13460540
10	295	Type 2	3.9	273	173.5	22	75	11	13460502
16	295	Type 2	3.9	273	173.5	22	75	14	13460522
25	310	Type 2	4.1	284	168	26	75	17	13460530

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Flange compression stage (PN)	Diameter bolt circle	Type of handle	Weight	A	C	D	E	T	Article
	mm		kg	mm	mm	mm	mm	mm	
40	320	Type 2	5.9	290	165	30	75	22	13460541
10	350	Type 2	3.2	328	181	22	75	13	13460503
16	355	Type 2	4	329	180.5	26	75	16	13460523
25	370	Type 2	6.2	340	175	30	75	21	13460531
40	385	Type 3a	9.4	352	169	33	75	27	13460542
10	400	Type 2	4.1	378	201	22	75	15	13460504
16	410	Type 2	5.4	384	198	26	75	18	13460524
25	430	Type 3a	9.1	400	190	30	80	24	13460532
40	450	Type 3a	14.5	417	181.5	33	80	31	13460543
10	460	Type 2	7.1	438	201	22	75	16	13460505
16	470	Type 2	10	444	198	26	75	21	13460525
25	490	Type 3a	14.9	457	191.5	33	80	27	13460533
40	510	Type 3a	22.7	474	183	36	80	35	13460544
10	515	Type 3a	8.9	489	215.5	26	75	18	13460506
16	525	Type 3a	12.2	495	212.5	30	75	23	13460526
25	550	Type 3a	19.6	514	203	36	80	30	13460534
40	585	Type 3a	34.5	546	187	39	80	40	13460545
10	565	Type 3a	10.9	539	190.5	26	75	20	13460507
16	585	Type 3a	17	555	182.5	30	75	26	13460527
25	670	Type 3a	23	564	178	36	80	32	13460535
40	685	Type 3a	31.5	571	174.5	39	80	41	13460546
10	620	Type 3a	13.8	594	223	26	75	22	13460508
16	650	Type 3a	22.4	617	211.5	33	75	28	13460528
25	660	Type 3a	3.8	624	208	36	80	36	13460536
40	670	Type 3a	39.9	628	206	42	80	45	13460547
10	725	Type 3a	18.2	695	223	30	75	25	13460509
16	770	Type 3a	35.4	734	211.5	36	80	33	13460529
25	770	Type 3a	43	731	208	39	80	41	13460537
40	795	Type 3a	63.2	747	206	48	100	53	13460548

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.