


## ECON® Needle valve fig. 2226 stainless steel with handwheel internal thread BSP



### Characteristics

**Type:** 2226  
**Norm:** EN (DIN)  
**Construction type:** Straight  
**Housing material:** Stainless steel  
**Material quality:** 1.4401  
**Connection:** Internal thread (BSPP)  
**Face to Face norm:** Manufacturer standard  
**Rotating needle:** Yes  
**Spindle material:** 1.4401

### Characteristics [2]

**Primary spindle seal material:** PTFE  
**Actuator material:** Plastic  
**Minimum medium temperature (continuous):** -10 °C  
**Maximum medium temperature (continuous):** 180 °C

Nominal inner diameter	Pressure rating	Face to Face length	Operation	Valve bore	Maximum pressure difference at 20 °C	Article
		mm		mm	bar	
1/4" [8]	PN420	50	Hand wheel	3	420	13455960
3/8" [10]	PN420	55	Hand wheel	4	420	13455961
1/2" [15]	PN420	60	Hand wheel	6	420	13411884
3/4" [20]	PN420	80	Hand wheel	8	420	13455962
1" [25]	PN420	80	Hand wheel	8	420	13455959

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.