

## STRAUB Pipe coupling Series: Open-Flex2 Type: 5534 Repair coupling Stainless steel/EPDM

Repair couplings for all pipe materials. Can also be used as a non-tensile pipe coupling. Depending on the opening, the couplings support a bending angle of 2° to 5° and axial movement of 10 mm. When installing, the locking screws must be tightened to the correct torque. The torque is specified on the coupling.

## **Field of application**

- Water distribution
- Gas pipelines
- Cooling water



- Repair coupling
- Suitable for both plastic and metal pipes
- Hinged pipe coupling
- Available in all pipe diameters between 180 and 2032 mm



## **Characteristics**

Series: Open-Flex2

**Type:** 5534

Shape: Repair coupling

Housing material: Stainless steel

Material quality: 1.4571 Sleeve material: EPDM Material bolts: Steel

Suitable for pipe material: Metal/plastic Suitable for plastic to metal: No

External tube diameter of connection	External tube diameter of connection 2	Pressure rating	Pressure rating Maritime	Minimum medium temperature (continuous)	Maximum medium temperature (continuous)	Article
mm	mm			°C	°C	
219.1	219.1	PN9	PN9	-20	70	12229676
273	273	PN7	PN7	-20	70	12229677

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.



15612510027442\_EN\_12.05.2024