



BURKERT Pneumatic actuated control valve Type: 2561 Series: 2301 Stainless steel EC1935 Internal thread




Characteristics

Series: 2301
Type: 2561
Function: Control valve
Construction type: Straight
Housing material: Stainless steel
Material quality: 1.4404
Process connection: Internal thread (BSPP)
Standard connection: DIN ISO 228-1
Ground characteristic: Equal percentage
Plug: Parabolic cone
Control range: 50:1
Leakage class: IV according IEC 60534-4
Stem seal type: PTFE
Material cone: Stainless steel 316 Ti [1.4571]
Seat material: Stainless steel 316 Ti [1.4571]

Spindle material: Stainless steel 316 [1.4408]
Type of actuator: Pneumatic
Function actuator: Spring closing
Positioner: Topcontrol 8692
Control signal: 4 - 20 mA
Level of protection (IP value): IP65/IP67
Medium temperature: -10 / 185 °C
Ambient temperature: -10 / 55 °C

Application

- Recommended in: Food & Beverages



Size table:

DN	Actuator	A mm	H mm	L mm	SW mm
3/8" [10]	R70	91	383	65	27
1/2" [15]	R70	91	383	65	27
3/4" [20]	R70	91	389	75	34
1" [25]	R70	91	392	90	41
1" [25]	R90	91	445	90	41
1.1/4" [32]	R90	120	473	110	50
1.1/4" [32]	R130	159	525	110	50
1.1/2" [40]	R130	159	530	120	55
2" [50]	R130	159	536	150	70

Nominal inner diameter	Size process connection	Pressure rating	Kvs value m³/h	Type coding actuator	Closing pressure bar	With feedback signal	Feedback signal	Article
DN10	3/8" [10]	PN16	2	R70	16	Yes	4 - 20 mA	13614318
DN10	3/8" [10]	PN16	2.7	R70	16	Yes	4 - 20 mA	13614319
DN15	1/2" [15]	PN16	2.1	R70	16	Yes	4 - 20 mA	13614320

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal inner diameter	Size process connection	Pressure rating	Kvs value m ³ /h	Type coding actuator	Closing pressure bar	With feedback signal	Feedback signal	Article
DN15	1/2" [15]	PN16	3.1	R70	16	Yes	4 - 20 mA	13614321
DN15	1/2" [15]	PN16	4.3	R70	16	Yes	4 - 20 mA	13614322
DN20	3/4" [20]	PN16	5.2	R70	16	Yes	4 - 20 mA	13614323
DN20	3/4" [20]	PN16	7.1	R70	16	Yes	4 - 20 mA	13614324
DN25	1" [25]	PN16	5.2	R70	16	Yes	4 - 20 mA	13614325
DN25	1" [25]	PN16	7.2	R70	16	Yes	4 - 20 mA	13614326
DN25	1" [25]	PN16	12	R90	16	Yes	4 - 20 mA	13614327
DN32	1.1/4" [32]	PN16	13.4	R90	16	Yes	4 - 20 mA	13614328
DN32	1.1/4" [32]	PN16	17.8	R130	16	Yes	4 - 20 mA	13614329
DN40	1.1/2" [40]	PN16	20.2	R130	16	Yes	4 - 20 mA	13614330
DN40	1.1/2" [40]	PN16	23.8	R130	16	Yes	4 - 20 mA	13614332
DN50	2" [50]	PN16	24.6	R130	16	Yes	4 - 20 mA	13614333
DN50	2" [50]	PN16	37	R130	16	Yes	4 - 20 mA	13614334

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.