

SMC One-touch Fittings Manifold series KM



Characteristics

Series: KM

Type: KM11

Primary connection	Primary thread size in	Secondary connection	Material	Max. operating pressure bar	Temperature °C	Article
						13523583
4 mm			PBT	10	-5 / 60	24126454
4 mm		4 mm	PBT	10	-5 / 60	24126460
4 mm		8 mm	PBT	10	-5 / 60	24126455
4 mm		8 mm	PBT	10	-5 / 60	24126443
4 mm		8 mm	PBT	10	-5 / 60	24126442
4 mm	R1/4		PBT	10	-5 / 60	24126449
4 mm	R1/4		PBT	10	-5 / 60	24126448
6 mm		6 mm	PBT	10	-5 / 60	24126462
6 mm		6 mm	PBT	10	-5 / 60	24126461
6 mm		10 mm	PBT	10	-5 / 60	24126444
6 mm		10 mm	PBT	10	-5 / 60	24126445
6 mm	R1/4		PBT	10	-5 / 60	24126451
6 mm	R1/4		PBT	10	-5 / 60	24126450
8 mm		8 mm	PBT	10	-5 / 60	24126456
8 mm		8 mm	PBT	10	-5 / 60	24126446
8 mm		8 mm	PBT	10	-5 / 60	24126447
8 mm	R3/8		PBT	10	-5 / 60	24126452
8 mm	R3/8		PBT	10	-5 / 60	24126453
10 mm		10 mm	PBT	10	-5 / 60	24126457
10 mm		10 mm	PBT	10	-5 / 60	24126458

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.