


PARKER Flow switch fig. 8110 plastic internal thread



Characteristics

Series: ESL
Type: 8110
Mounting: Horizontal and vertical
Internal spring: Yes
Process connection: Internal thread [BSPP]
Calibration: Oil
Accuracy: 5.0 %
Material of connection: Fiber reinforced nylon
Housing material: Fiber reinforced nylon
Sealing: NBR
Spring material: Stainless steel
Material float catcher: Fiber reinforced nylon
Number of contacts: 1



Characteristics [2]

Contact type: Reedcontact
Switching power: 300V / 2,5 A / 100 W [res] 70 W [ind]
Electrical connection: Plug EN 175301-803 type A
With needle valve: No
Explosion-proof: No
Medium temperature: 5 / 80 °C
Ambient temperature: -5 / 80 °C

Size process connection	Measuring range	Measuring unit	Material measuring tube	Float material	Max. pressure bar	Article
1" [25]	1 / 15	l/min	Borosilicate	Acetal	10	13461229
1" [25]	2 / 30	l/min	Borosilicate	Acetal	10	13461230
1" [25]	5 / 100	l/min	Borosilicate	Acetal	10	13461232
1" [25]	10 / 150	l/min	Borosilicate	Acetal	10	13461233
1" [25]	4 / 50	l/min	Borosilicate	Acetal	10	13461231

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.