

FLEXION Hose retaining system retrofit FL-HRS-R



Characteristics

Type: FL-HRS-R

Material: Steel/brass

Surface protection: Zinc Plated

Maximum temperature: 150

Performance: Mountable without hose cut-off

Maximum operating pressure bar	Hose ID [DN]	For hose diameter	Connection, equipment side	Article
DN02 up to 630 bar, DN03 up to 500 bar, DN04 up to 450 bar	DN02 - DN04	4.5-8.5	7.5-11.5	13160089
DN02 up to 630 bar, DN03 up to 500 bar, DN04 up to 450 bar	DN02 - DN04	4.5-8.5	7.5-11.5	13160088
DN02 up to 630 bar, DN03 up to 500 bar, DN04 up to 450 bar	DN02 - DN04	4.5-8.5	7.5-11.5	13160090
450	DN05 - DN08	11-19	12-20	13160091
450	DN10 - DN12	17-28	18-24	13160092
420	DN16	23-31	22-30	13160093
420	DN19	26-35	28-36	13160094
420	DN25	34-44	32-42	13160095
350	DN31 - 4SH	43-52	38-52	13160099
310	DN38 - 4SH	50-61	44-52	13160100
270	DN51 - 4SH	60-74	56-62	13160101

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.