

FLEXION Hose retaining system FL-HRS-E



Characteristics

Type: FL-HRS-E

Material: Steel/brass

Surface protection: Zinc Plated

Performance: No sharp corners or edges. PA steel cable protection

Maximum operating pressure bar	Hose ID [DN]	For hose diameter	Connection, equipment side	Article
450	DN05 - DN08	11-19	6L	13160062
450	DN05 - DN08	11-19	8L - 6S - 1/4	13160061
450	DN05 - DN08	11-19	10L - 8S - 3/8	13160063
445	DN08 - DN10	14-23	12L - 10S	13160064
445	DN08 - DN10	14-23	12S	13160065
445	DN10 - DN12	17-28	16S	13160066
420	DN16 - DN19	23-35	18L - 3/4	13160067
420	DN19 - DN25	26-44	1	13160068
420	DN19 - DN25	26-44	28L - 25S	13160069
420	DN19 - DN25	26-44	30S	13160070
325	DN31 - 4SH	43-52	1 1/4	13160071
325	DN31 - 4SH	43-52	35L	13160072
325	DN31 - 4SH	43-53	38S	13160074
290	DN38 - 4SH	50-61	1 1/2	13160073
290	DN38 - 4SH	50-61	2	13160075

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.