

3M Scotch-Brite Surface Conditioning Laminated Sanding Disc SC-FD

Design: With aluminium oxide fleece segments (A). Because the layers have been directly applied to a fibreglass underlay they can be used on angle grinders without additional backing pads.

Application: The discs deliver the best results on steel, stainless steel, aluminium and non-ferrous metals. For de-rusting and cleaning on flat metal parts, surface preparation for laminates and paints as well as for creating a decorative finish.

Description	Article
Flap grinding wheel fleece SC-FD 115mm coarse	12064119
Flap grinding wheel fleece SC-FD 115mm medium	12064120
Flap grinding wheel fleece SC-FD 115mm veryfine	12064121
Flap grinding wheel fleece SC-FD 125mm coarse	12064122
Flap grinding wheel fleece SC-FD 125mm medium	12064123
Flap grinding wheel fleece SC-FD 125mm veryfine	12064124

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

ERIKS

PR_EC000173_0548_MVB_EN_11.05.2024

ERIKS BV