# 3M MDT-A medium wall thickness heat shrink tubing (hot-melt adhesive)

Balances electrical, physical and chemical properties for various industrial applications
Offers shrink-fit protection and strain relief of wires, solder joints, terminals and connections
Suitable for lightweight wire-harness covering, wire marking, wire bundling and component packaging
Made of flexible polyolefin
Withstands temperatures of -55 to 130 degrees C
Halogen free

| Description | Article |
|---|---|
| Heat-shrink tubing Medium-walled MDT-A Ø19-6mmx1m, black | 11965135 |
| Heat-shrink tubing Medium-walled MDT-AØ32-7,5mmx1m, black | 11965137 |
| Heat-shrink tubing Medium-walled MDT-AØ38-19mmx1m, black | 11965138 |
| Heat-shrink tubing Medium-walled MDT-AØ70-26mmx1m, black | 11965140 |
| Heat-shrink tubing Medium-walled MDT-AØ90-36mmx1m, black | 11965141 |
| MDT-A medium wall thickness heat shrink tubing (hot-melt adhesive) | 11965133 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.



ERIKS BV | Tel: +31 88 855 81 70 | E-mail: gereedschappen@eriks.nl