

DIN966H Raised countersunk head screw with Phillips cross recess Stainless steel A2



Characteristics

Series: DIN 966H
Head form: Countersunk head (oval)
Screwing system: Phillips
Material quality: Stainless steel A2
Surface protection: Untreated
DIN standard: 966
ISO standard: 7,047
Type: Stud bolt

Material	Kind of thread	Thread size metric [M..]	Pitch thread	Length mm	Article
Stainless steel	Metric	2.5	0.45	10	23729282
Stainless steel	Metric	3	0.5	6	23729290
Stainless steel	Metric	3	0.5	10	23729284
Stainless steel	Metric	3	0.5	16	23729286
Stainless steel	Metric	4	0.7	8	23729301
Stainless steel	Metric	4	0.7	10	23729292
Stainless steel	Metric	4	0.7	12	23729293
Stainless steel	Metric	4	0.7	16	23729294
Stainless steel	Metric	4	0.7	20	23729295
Stainless steel	Metric	4	0.7	25	23729296
Stainless steel	Metric	4	0.7	30	23729297
Stainless steel	Metric	4	0.7	40	23265499
Stainless steel	Metric	4	0.7	60	23729300
Stainless steel	Metric	5	0.8	12	23729303
Stainless steel	Metric	5	0.8	60	23729311
Stainless steel	Metric	6	1	16	23729316
Stainless steel	Metric	6	1	25	23729318
Stainless steel	Metric	8	1.25	25	23729325

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.