

## FENWAL Precision thermostat fig. 3810 type 18000

### Characteristics

**Series:** 18000

**Type:** 3810

**Model:** Precision thermostat


**Connection:** External thread (NPT)

**Size process connection:** 1/2" (15)

**Maximum contact load:** 5 A

**Electrical connection:** Lead wires

**Explosion-proof:** No



| Adjustment range | Adjustment range °F | Insert length | Sensor diameter | Process connection material | Housing material | Sensor material | Switching function      | Medium temperature | Article  |
|------------------|---------------------|---------------|-----------------|-----------------------------|------------------|-----------------|-------------------------|--------------------|----------|
| °C               | °F                  | mm            | mm              |                             |                  |                 |                         | °C                 |          |
| -73 / 315        | -100 / 600          | 75.4          | 15.88           | Brass                       | Brass            | Stainless steel | Break (normally closed) | -73 / 370          | 10060504 |
| -73 / 315        | -100 / 600          | 75.4          | 15.88           | Brass                       | Brass            | Stainless steel | Make (normally open)    | -73 / 370          | 10060506 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.