



WEG 3 Phase motor W22Xdb Cast Iron B35T (2p)

Flameproof motors designed to meet the latest market requirements and certifications for Hazardous Areas. Offer high efficiency, low noise and vibration levels and allow applications in severe duties.

Characteristics

Series: W22Xdb

Type: B35T

Speed: 3000 rpm

Mounting: B35T

Number of poles: 2

Full load speed: 2960 rpm

Full load torque: 9.947 Nm

Nominal rated frequency: 50 Hz

Material: Cast iron

PTC thermistor: Yes

Energy efficiency class	Power kW	ATEX Zone	Nominal rated voltage V	Frame size acc. to IEC	Article
IE2	0.37	Zone 1	230/400	71	12962315
IE2	0.55	Zone 1	230/400	71	12962320
IE3	0.37	Zone 1	230/400	71	13192227
IE3	0.55	Zone 1	230/400	71	13192232
IE3	0.75	Zone 1	230/400	80	13192237
IE3	1.1	Zone 1	230/400	80	13192242
IE3	1.5	Zone 1	230/400	90S/L	12962886
IE3	2.2	Zone 1	230/400	90S/L	13192247
IE3	3	Zone 1	230/400	100L	13192252
IE3	4	Zone 1	400/690	112M	13192257
IE3	5.5	Zone 1	400/690	132S/M	13192262
IE3	7.5	Zone 1	400/690	132S/M	13192267
IE3	9.2	Zone 1	400/690	132S/M	13192272
IE3	11		400/690	132M	12767312
IE3	11	Zone 1	400/690	160M/L	13192275
IE3	15	Zone 1	400/690	160M/L	13192279
IE3	18.5	Zone 1	400/690	160M/L	13192282
IE3	22	Zone 1	400/690	180M/L	13192285
IE3	30	Zone 1	400/690	200M/L	13192288
IE3	37	Zone 1	400/690	200M/L	13192291
IE3	45	Zone 1	400/690	225S/M	13192294

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.