



WEG 3 Phase motor W22Xdb Cast Iron B34T (2p)

Flameproof motors designed to meet the latest market requirements and certifications for Hazardous Areas. Offer high efficiency, low noise and vibration levels and allow applications in severe duties.

Characteristics

Series: W22Xdb

Type: B34T

Speed: 3000 rpm

Mounting: B34T

Number of poles: 2

Full load speed: 2910 rpm

Full load torque: 9.947 Nm

Nominal rated frequency: 50 Hz

Material: Cast iron

PTC thermistor: Yes

Energy efficiency class	Power kW	ATEX Zone	Nominal rated voltage V	Frame size acc. to IEC	Article
	4				14063241
IE2	0.37	Zone 1	230/400	71	12962317
IE2	0.55	Zone 1	230/400	71	12962322
IE3	0.37	Zone 1	230/400	71	13192226
IE3	0.55	Zone 1	230/400	71	13192231
IE3	0.75	Zone 1	230/400	80	13192236
IE3	1.1	Zone 1	230/400	80	13192241
IE3	1.5	Zone 1	230/400	90S/L	12962888
IE3	2.2	Zone 1	230/400	90S/L	13192246
IE3	3	Zone 1	230/400	100L	13192251
IE3	4	Zone 1	400/690	112M	13192256
IE3	5.5	Zone 1	400/690	132S/M	13192261
IE3	7.5	Zone 1	400/690	132S/M	13192266
IE3	9.2	Zone 1	400/690	132S/M	13192271

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.