RX Safety shoe RX Securo S3



Composite toe cap to 200 J. Anti-perforation midsole made from MS3 textile; very flexible, gives a much better walking comfort, isolates against the cold and/or heat and protects a larger area of the foot. Scuff pad allows more 'give' at the point where the foot flexes. Ideal for jobs where kneeling is required. Quality uppers stabilises and supports the foot. TPU heel support. Reflective accents for high visibility. Shock-absorbing comfort sole for better walking comfort. PU/rubber sole material; oil and petrol resistant. HRO resistant to 300° C contact heat. SRC sliip resistance. Ladder grip prevents slipping on ladders. Extra Wide Fit (10).

Characteristics

Series: SECURO S3

Norm: EN 20345 S3 HRO SRC

Safety class: S3

Mid-sole protection: Yes

Protection class occupational shoes	ОВ	01	O2	О3	04	О5
Protective toecap						
Energy absorption in heel		*	*	*	*	*
Fully enclosed heel		*	*	*	*	*
Antistatic properties		*	*	*		
Puncture resistant outsole				*		
Water penetration and absorption protection			*	*	*	*
Water resistant						

Protection class safety shoes	SB	S1	S1P	S2	\$3	S4	S 5
Protective toecap	*	*	*	*	*	*	*
Energy absorption in heel		*	*	*	*	*	*
Fully enclosed heel		*	*	*	*	*	*
Antistatic properties		*	*	*	*	*	*
Puncture resistant outsole			*		*		*
Water penetration and absorption protection				*	*	*	*
Water resistant						*	*

Shoe size	Shoe size (UK)	Model	Width	Material toecap	Heat resistant outsole	Antistatic	Slip resistance	Article
40	6.5	Low shoe	10	Composite	300°C	Yes	SRC	12342006

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR_EC002104_0002_EN_05.05.2024