



GESIPA Blind rivet gun TAURUS-2 pneumatic-hydraulic type 9316

Design: With integrated protection device against mandrels flying out. The receptacles for the alternate mouthpieces are located in the bottom of the device. The compressed air used for the setting process is also used to suck up the rest of the mandrel. The new gripper jaw system increases the service life many times over. The trailing port prevents being affected by the hose. The rivet suction can only be switched on by lifting the machine. Retractable suspension bracket on the head. Coordinated device lift for quick work sequences with removable mandrel-collecting container.

Application: For all materials up to Ø 5 mm and aluminium/steel up to Ø 6 mm (max. mandrel Ø 3.2 mm).

Nosepiece attachment:

Rivet Ø; rivet materials; nosepiece

2.4; Alu; 17/18

3.2; CAP-Alu, Cap-Cu; 17/18

3; Alu/Cu; 17/20

3 and 3.2; Alu, Cu, steel, stainless steel, Stinox, Alu/Alu, PG-Alu, PG-steel; 17/24

4; Alu, Cu, CAP-Alu, CAP-Cu; 17/24

4; steel, Alu/Alu, PG-Alu; 17/27

4; stainless steel, Stinox, PG-steel; 17/29

4.8 and 5; Alu, CAP-Alu, CAP-Cu, PG-Alu; 17/29

4.8 and 5; steel, Alu/Alu; 17/32

4.8 and 5; stainless steel, Stinox, PG steel; 17/36

6; Alu; 17/36

6; steel; 17/40

6.4; Alu; 17/40

6.4; steel, Alu/Alu; 17/45

8; Alu; 17/45

Scope of delivery: Blind rivet pistol TAURUS® 2, 4 nosepieces 17/27, 17/29, 17/32, 17/36, 2 assembly key SW 12/14, 14/17, 1 bottle of hydraulic oil 100 ml, 1 oil refill container.

Operation	Article
	12152943
	14591795
	14591794
Electrical	23429535

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.