

FACOM Torque wrench with detachable ratchet type no. 306A



- STANDARDS: NF EN ISO 6789, ISO 6789, DIN EN ISO 6789
- Factory accuracy: $\pm 2\%$ except: - R.306-25D - K306-600D - K306-1000D ($\pm 4\%$). - R.304DA ($\pm 6\%$).
- Reliability of mechanism: 50 000 cycles (wrenches up to 200 N.m).
- Use possible with accessories: - End fitting: 9 x 12 or 14 x 18 mm. - Diameter: 30 mm.
- One-way wrenches usable for unscrewing by reversing the bits.
- Numbered wrenches supplied with ISO 6789 calibration certificate.
- Supplied in a plastic box with ratchet and hinged handle [except Ref R.306A25 - R.301A - K.306A600 - K.306A1000].

Characteristics

Type: 306A

Connection size	Tightening moment Nm	Total length mm	Weight g	Article
1/2	20 / 100	437	1000	23447960
1/2	40 / 200	515	1300	23447961
1/2	70 / 350	725	1800	23447963
1/4	5 / 25	271	450	23447956
3/8	10 / 50	375	930	23447958
3/8	20 / 100	437	1000	23448294

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.