


FORMAT 3-part hand tap set HSS metric type 1604



Design: HSS, DIN 352, tolerance range ISO 2/6H, type N, bright surface.

Application: For regular metric threads according to ISO DIN 13. Particularly suitable for high strength materials up to 1200 N/mm² in strength and rust-free and acid-resistant steels.

Set consisting of [order no. 1600, 1601, 1603].

Characteristics

Kind of thread: Metric

DIN standard: 352

Kind of thread	Thread size metric (M...)	Pitch inner thread	DIN standard	Material	Total length	Article
		mm			mm	
Metric	1		352	HSS		23411653
Metric	1.2		352	HSS		23411654
Metric	1.4		352	HSS		23411655
Metric	1.6		352	HSS		23411656
Metric	1.7		352	HSS		23411657
Metric	2		352	HSS		23100800
Metric	2.2		352	HSS		23411659
Metric	2.3		352	HSS		23411660
Metric	2.5		352	HSS		23411661
Metric	2.6		352	HSS		23411662
Metric	3.5		352	HSS		23411664
Metric	4		352	HSS		23100803
Metric	4.5		352	HSS		23411666
Metric	5		352	HSS		23100804
Metric	6		352	HSS		23100805
Metric	7		352	HSS		23411669
Metric	8		352	HSS		23100806
Metric	9	1.25	352	HSS	63	23411671
Metric	10		352	HSS		23100807
Metric	11		352	HSS		23411673
Metric	14		352	HSS		23100809
Metric	16		352	HSS		23100810
Metric	18		352	HSS		23100811
Metric	20		352	HSS		23100812
Metric	22		352	HSS		23100813
Metric	24		352	HSS		23100814
Metric	27		352	HSS		23100815
Metric	30		352	HSS		23411682
Metric			352	HSS		23100802
Metric			352	HSS		23100808

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.